

Nano-Clear[®] Stone Impregnator



COATING BENEFITS:

- Permanently Enhances Color
- Prevents Stains and Water Damage
- Highly Weather Resistant
- Restores, Protects and Preserves
- 10 Year Performance Warranty

PRODUCT DESCRIPTION

Designed for professional use only.

Nano-Clear Stone Impregnator permanently enhances, restores and protects brick pavers, clay roof tiles, travertine, natural and artificial exterior stone. Nano-Clear will not fade, peel or power-wash away. Nano-Clear is a solvent borne 1K polyurethane "cross-linked" nanocoating. Nano-Clear permanently / chemically bonds to porous stone surfaces.



Application Instructions: It is important to review the Nano-Clear Stone Impregnator MSDS prior to use. Use only as directed. Test in a small inconspicuous area before full application.

1. Remove surface contaminants including sealers, coatings and waxes with approved stone stripper.
2. Ensure that stone surface is completely dry for 24 – 48 hours prior to applying Nano-Clear.
3. Apply when relative humidity should be between 20% and 80%. Temperature should be between 45°F and 85°F.
4. It is important to ensure that the application area is well-ventilated during application. Keep children and animals out of the area until Nano-Clear during spray application.
5. Wear solvent resistant rubber gloves and an approved paint respirator when spraying in large areas.
6. Mask off all important surfaces that are not intended to be coated. Nano-Clear will adhere to most surfaces.
7. Apply even wet-coats using a brush, roller, pump-up garden sprayer or airless spray equipment.
8. Allow Nano-Clear to penetrate surface for 5 – 10 minutes between wet-coats. More dense stone may require more wet coats and time to penetrate. It is important "not" to allow excess Nano-Clear to cure on the surface.
9. Wipe out any high spots or excess Nano-Clear Coating with a dry microfiber cloth.
10. If a darker appearance is required, a second, third or fourth wet-coat of Nano-Clear may be applied within 5 – 10 minutes between each wet-coat.
11. Nano-Clear fully cures within 24 hours. Avoid foot traffic or rain for a minimum of 6 hours after application.
12. Close container immediately after use to avoid moisture contamination. Do not leave cap open for extended periods.
13. Equipment must be cleaned immediately after application with paint thinner or acetone. Otherwise, the container will become un-useable. Dispose of any towels or rubber gloves used in accordance with local waste disposal regulations.

SURFACE COVERAGE

1,040 sq. ft. per gallon (depending on porosity of stone surface).

VOC CONTENT

1.25 lbs. / gal.

